



Lay-Flat Diesel & Long Term Potable Water Tank.



The JW Automarine Lay-Flat Flexi-Tainer is approved for long term storage of potable water and diesel in extreme environments. Manufactured from a heavy duty polyurethane coated polyamide base cloth, which gives high abrasion and UV resistance, the standard capacity range is from 1,000 to 300,000 Litres. We also provide a bespoke design and manufacture of tanks to suit your requirements. Each tank has various options of inlet and outlet valves. All tanks are fitted with air vents and webbing loop securing straps. Other options include a ground sheet or bund liner. All tanks are manufactured and certificated in accordance with the current EN ISO 9001:2000 quality standard .

Technical Specifications

Material Type - Sand / Black PU				
Model Number	Capacity (Litres)	Filled Height (M)	Empty Length (M)	Empty Width (M)
SP1000PULFT	1,000	0.6	1.65	1.96
SP2000PULFT	2,000	0.8	2.56	1.96
SP3000PULFT	3,000	0.8	2.28	2.94
SP4000PULFT	4,000	0.8	2.82	2.94
SP5000PULFT	5,000	0.8	3.36	2.94
Material Type - Yellow / Grey PU				
Model Number	Capacity (Litres)	Filled Height (M)	Empty Length (M)	Empty Width (M)
SP6000PULFT	6,000	1	3.5	3.07
SP8000PULFT	8,000	1	4.33	3.07
SP10000PULFT	10,000	1	4.1	3.84
SP12000PULFT	12,000	1	4.75	3.84
SP15000PULFT	15,000	1	4.75	4.61
SP20000PULFT	20,000	1	6.05	4.61
SP25000PULFT	25,000	1	6.5	5.37
SP30000PULFT	30,000	1.2	6.75	5.37
SP40000PULFT	40,000	1.2	7.4	6.14
SP50000PULFT	50,000	1.2	9	6.14
SP60000PULFT	60,000	1.2	9.4	6.91
SP80000PULFT	80,000	1.2	10.9	7.68
SP100000PULFT	100,000	1.2	11.1	9.21
SP150000PULFT	150,000	1.2	13.75	10.74
SP200000PULFT	200,000	1.2	15.7	12.28
SP300000PULFT	300,000	1.2	20	14.58

Advantages

Strong, flexible, versatile and easy to deploy.
Reinforced construction to ensure reliability.
Easy to repair.
Folded compactly for easy storage and transport.
Excellent resistance to extreme weather conditions, abrasion, corrosion and long term standing use.
Sizes range from 1,000 Litres to 300,000 Litres.
Draining is achieved quickly and easily via gravity flow.

Applications

- Diesel Storage
- Oils storage
- Foam concentrates
- Emergency water storage
- Potable water storage
- Remote storage
- Chemical waste
- Fertilisers



All of JW Automarine's products are manufactured in accordance with **EN ISO 9001:2000**

Quality Certifications

EN ISO 9001:2000 Certificate Number GB93/1901